

## Extension Cord with Drum

### Application

For powering household electrical appliances. The extension cords are made in accordance with the regulations for low voltage equipment, with the essential safety requirements for the application of the CE marking



### Construction

Cord plug	Schuko
Cord	H05VV-F 3G1.5
Drum	Model 6680, 6681

### Standards and Certifications

CEI 884-1+A1:1997, DIN 49441, VDE 0281-5 / HD 21.5 S3

Cord: EN 50525-2-11

Plug - VDE



Cord - VDE HAR



### Technical Data

Nominal voltage U <sub>0</sub> /U	[V]	250
Nominal current	[A]	16
Maximum power	[W]	3800
Temperature range	°C	-40°C till +70°C
Operating temperature	short circuit°C	150°C
Short circuit time	max. [sec]	5
Bending radius	x diameter	5

Extension Cord with Drum

Technical data, dimensions and weights are subject to change. All sizes and values without tolerances are reference values. Specifications are for products supplied by ROMCAB: any modification or alteration of products may give different results. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Romcab S.A. The information is correct to the best of our knowledge at the time of publication. Romcab S.A. reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorized by Romcab. © All rights reserved by ROMCAB S.A • www.Romcab.com

## **Drum Dimensions**

Model 6680: 180 x 230 x 300 mm with H05VV-F 3x1.5 length 30m

Model 6681: 220 x 290 x 375 mm with H05VV-F 3x1.5 length 50m